



SABA Primer 9002

primer for various substrates

Description

SABA Primer 9002 is a 1-component primer for pre-treating various substrates.

Field of application

The marine, transport, building and industry sectors. SABA Primer 9002 is very suitable for pre-treating porous and non-porous substrates, metals and plastics. Also suitable as a varnish for Sabatack products.

Advantages

- offers good paint adhesion for Sabatack which is cured
- excellent adherence to porous substrates
- free of isocyanates
- conforms to EN 14188-4

Method of use

For instructions for use, see the relevant info sheets on www.saba.nl

Seal the container as soon as possible after use; this has a positive effect on the processing properties and the shelf life of the product.

Technical data

Basis	polyacrylate with silanes
Viscosity at 23 °C (EN 12092)	approx. 15 mPa.s
Density (EN ISO 2811-2)	approx. 930 kg/m ³
Solids content	approx. 11 %
Flashpoint	approx. + 28 °C
Solvents	mixture of alcohols and aromatics
Open time	15 minutes to 4 hours
Coverage	approx. 100 g/m ²
Working temperature	min. + 5 °C to max. + 35 °C
Storage temperature	min. + 5 °C to max. + 35 °C
Temperature resistance	min. - 40 °C to max. + 120 °C

Order information

Packaging	can with resealable lid
Contents	250 ml (contains 12 items)
Colour	transparent
Article no.	100482 AAQ
Shelf life	12 months (in unopened packaging)

Other packaging on request. The shelf life may vary for large packaging.

Safety recommendations

For more information about safety, see the relevant SABA safety data sheet.